

# SYLPIPE L600 950LM 830 HIGH OUTPUT

Item No: 0090052

**SYLVANIA**

YourHome



LED T5 replacement batten, high output range: more lumens per meter with efficiency up to 125 lum/watt, seamless linking (up to 10M), ideal for direct lighting such as under cabinet or in kitchens, 120 degree beam angle, includes switch, includes 0.30m stripped cable, white polycarbonate body, includes standard and tilting brackets

## Technical Assets

### Photometrics

#### General data

Product name	SYLPIPE L600 950LM 830 HIGH OUTPUT
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
General application	Residential & Consumer, Retail
ETIM Class	EC000109
E-number FI	4279463
Warranty	3 years

#### Optical data

Fixture luminous flux (lm)	950
Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	80
Beam Angle (°)	120
Photobiological Risk Group	RG1

#### Electrical data

Total power consumption (W)	8
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.5
Electrical protection	Class II
Control gear required	No
Control gear type	Not required
Dimmable	No
Dimming method	N/A
Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	50/60Hz
Connectable conductor cross section - Max (mm <sup>2</sup> )	0.75

# SYLPIPE L600 950LM 830 HIGH OUTPUT

Item No: 0090052

**SYLVANIA**

## Lifetime data

Lifespan L70 B50 | 54000

Lifespan L80 B10 | 54000

## Physical data

Housing colour | White

IP rating | IP20

IK rating | IK03

Nominal Product Length (mm) | 600

Nominal Product Width (mm) | 24

Nominal Product Height (mm) | 35

Weight (kg) | 0.101

## Packaging

Product EAN number | 5410288900520

Packaging single length / height (cm) | 75.3

Packaging single width (cm) | 3.2

Packaging single depth (cm) | 4.2

DUN14 (inner) | 15410288900527

Units per outer package | 40

Packaging outer length / height (cm) | 77.5

Packaging outer width (cm) | 23.5

Packaging outer depth (cm) | 28.7

## Safety data

Glow Wire Test (°C) | 650