

Type

Latex-free and odourless water-borne primer for exterior use. Uula Exterior Prime is safe, eco-friendly and easy to use. Improves adhesion, dries fast and is breathable with the wood. Renewable natural oils work as the binder.

Intended use

Sawn and planed wooden surfaces, also log and impregnated exterior wood surfaces.

Technical qualities

Gloss grade: Matt.
Density approx. 1.3 kg/L.
Does not contain any VOC.
Nonflammable

Colours

White and tints made to A- and C-bases according to Uula colour chart. Can be tinted according to most common colour charts.

Application & conditions

Ordinary paint brush, paint roller or high-pressure paint sprayer. The surface must be dry and the moisture content of the wood below 15 %. the relative air humidity below 80 % and the temperature at least +5°C.

Drying time

Tack-free in approx. 30 minutes. Can be painted over after 6 hours. (+20°C and <80 % relative humidity)

Coverage

Planed surface 8–12 m²/L, sawn surface 6–8 m²/L.

Cleaning of equipment

Clean the equipment with soap and water right after you have finished painting.

Thinner

Water

Container sizes

0.9 L, 2.7 L and 9 L.

Storage and disposal

Keep in a cool and dry place. Do not allow to freeze!
Dry and empty containers can be taken to a refuse dump.
Liquid waste must be taken to a municipal hazardous waste collection point.

Painting instructions:

Preparations

Clean the surface from dirt and dust. Remove peeling and flaking old paint with wire brush and scraper. Wash dirty surfaces with Uula Paint Washing Agent and mouldy ones with mould washing solution. Sand a new planed surface rough before priming to ensure adhesion.

Priming

Paint with Uula Exterior Primer. Let dry for 6 hours.

Finishing

According to the instructions of the desired paint type.

Points to note

- *Stir well before use and during painting
- *Do not paint in rain, direct sunlight or on sun heated surfaces
- *You can dilute the paint 15 % with water when painting the boards separately.
- *When using high-pressure paint spray, pre-treatment according to the surface. Size of spray nozzle 0,5mm and thinning 0-10 % if needed.
- *If surface becomes dirty due to climatic effects, wash the surface
- *More detailed instructions for maintenance and cleaning can be found in our website www.uula.fi
- *In case of uncertainty, submit to the manufacturer of the paint or to a competent distributor before starting the painting process.

Information in the technical specification is based on tests and practical experience. All instructions are only indicative and depend, for example, on the texture of the surface, quality, colour and previous treatments. Because we cannot control the use and working conditions of our products we take responsibility only for the quality of the product and guarantee that it is in accordance with the high standards of Uulatuoite Oy. We do not take responsibility for damage caused by using the product against our instructions or intended use.