

ToLEDo G9 ToLEDo RT G9 CL 250LM 827 SL 0028476



Product features

- LED retrofit replacement for halogen mains voltage capsules
- ToLEDo Retro G9 has the same look and feel as halogen design thanks to glass construction body and wide light distribution
- Compact design
- Omni-directional light distribution
- 250lm = 25W halogen G9 lamp
- 90% energy saving
- A++ energy rating
- Non-dimmable
- Suitable for chandeliers, interior display, shop windows, decorative and general lighting applications









NOTES

undefined

PRODUCT OVERVIEW

Product name	ToLEDo RT G9 CL 250LM 827 SL
Technology	LED
Watt (Rated) (W)	2
Cap/Base	G9
Fixture rating	Open
General application	Hospitality, Residential & Consumer
ETIM Class	LED-lamp/Multi-LED
E-number FI	4740823
Warranty	3 years
Luminous flux (lm)	250



ToLEDo G9 ToLEDo RT G9 CL 250LM 827 SL 0028476

Colour temperature (K)	2700
Light colour	Homelight
CRI (Ra)	80
Wattage (W)	2
Product Voltage (V)	230
Average life (Nominal) (h)	15000
Product EAN number	5410288284767

DATA TABLE

TA TABLE	
General data	
Product name	ToLEDo RT G9 CL 250LM 827 SL
Technology	LED
Watt (Rated) (W)	2
Cap/Base	G9
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Performance ambient temperature Tq (°C)	25
ETIM Class	LED-lamp/Multi-LED
E-number FI	4740823
Warranty	3 years
Optical data	
	050
Luminous flux (lm)	250
Luminous flux (Rated) (Im)	250
Colour temperature (K)	2700
Light colour	Homelight
CRI (Ra)	80
Lumen maintenance at end of nominal life (%)	70
(70)	
Electrical data	
Wattage (W)	2
Equivalent watt (W)	25
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	1
Product Voltage (V)	230
Lamp power factor	0.8
No. Of switching cycles before premature failures	>50000
Inrush Current (A)	0.6
kWh per 1000 hours burning time	2
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	50
Max. Luminaires per 16A C Breaker	80
Max. Luminaires per 20A C Breaker	100
•	



ToLEDo G9 ToLEDo RT G9 CL 250LM 827 SL 0028476

Lifetime data	
Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000
Physical data	
Nominal Product Length (mm)	49
Nominal Product Diameter (mm)	13
Weight (kg)	0.007
Packaging	
Single packaging type	Carton
Product EAN number	5410288284767
Packaging single length / height (cm)	2.0
Packaging single width (cm)	2.0
Packaging single depth (cm)	6.5
DUN14 (outer)	15410288284764
Units per outer package	10
Packaging outer length / height (cm)	15.5
Packaging outer width (cm)	6.5
Packaging outer depth (cm)	7.2
2 (
Safety data	
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures